



POLIPASTO CADENA P80

Pivot and swivel top hook for easy rigging



Automatic double pawl braking system to secure loads at any height

Enclosed gear housing suitable for outdoor use

Channeled guide slots guard against jamming and slipping

Black anodized grade 80 chain certified for vertical lifting



Swivel hook with high-strength locking fasteners

Features:

- Guide slots guard against jamming and slipping
- Roller and ball bearing construction reduces friction
- Automatic double pawl-braking system
- Hardened swivel latch hooks
- Self-locking lever controls the pulling direction
- 360° handle rotation and pivot & swivel top hook for easy rigging
- All-steel construction for extreme durability
- Hook is assembled with high-strength locking fasteners
- Rubber handle grip on lever for comfort and anti-skidding
- One-hand operation with the best free chaining available

Self-locking lever controls the pulling direction with neutral position for free spooling

360 degree handle rotation

Comfortable rubber grip handle

POLIPASTO CADENA P80

POLIPASTO CADENA P80

Model	HSB-7.5CB	HSB-15CB	HSB-30CB	HSB-60CB
Rated load (T)	0.75	1.5	3	6
Test load (T)	0.95	1.875	3.75	7.5
Standard lift (m)	1.5	1.5	1.5	1.5
Min. distance between two hooks(mm)	290	385	477	550
Efforts required at capacity (N)	196	220	325	343
No. of load chains	1	1	1	2
Diameter of load chain (mm)	6x18	8x24	10x30	10x30
Dimensions	A	148	174	193
	B	135	160	209
	C	295	423	423
	H	290	385	477
Extra weight per meter of extra lift(kg)	0.82	1.43	2.21	4.42
Net weight (kg)	7	11	20	30

