



West Bussines Park
Bulgaria street, module 1.6
PC: 11011 - Cadiz - Spain

Tel: +34-956074747
Fax: +34-956279657
jramirez@rmglobaltrade.com

VISOR TONO 5

MODELO: FC48G5

Item No.	FC48G5
Product Name	UV Protection Visor
Standards	EN166 ANSI Z87.1
Thickness	1.0 mm
Size	8" x 15½" (20 cm x 39 cm)
Material	Polycarbonate
Color	Dark Green
Scale number for filters	CE 2-5 ANSI U5
Packaging	35 pcs/inner box 140 pcs/carton



/ Best optical quality

To provide users with the best vision possible and help them better focus on their task, Blue Eagle faceshields have passed the highest levels of optical tests (Class 1), including spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion.

/ Protective films

Both sides of the visors are furnished with protective films to ensure protection against damage or scratches during transportation. These films can be easily removed before use.

/ Impact resistance

Includes frontal and lateral impact resistance.

/ High-speed particle impact resistance, 120 m/s

The faceshield is made using extrusion-grade polycarbonate (PC) with the highest specifications for mechanical strength, allowing it to withstand the impact of a 6 mm steel bead traveling at a speed of 120 m/s.

/ Superb UV protection

We used advanced technologies to provide the user with superb protection against UV.

/ Resistance to ignition

European Standard testing was used. An iron rod measuring 6 mm in diameter and 300 mm in length was heated at one end to a temperature of 650°C. The heated end was pressed against the sample surface using its own weight for 5 seconds. The faceshield did not catch fire nor glow red.

/ Quick and easy visor replacement

/ Made in Taiwan



Date

Signature